Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

| sources | ELEGATED REGUL | -AHON (EU) 2019/2 | 2015 with regard to ener | gy labelling of light | | |
|--|------------------|----------------------------|--|-----------------------|--|--|
| Supplier's name | e or trade mark: | Rábalux | | | | |
| Supplier's address: Magyarország - Rábalux Világítástechnika Zrt., Körtefa 5., 9027 Győr, HU | | | | | | |
| Model identifie | r: 76019 | | | | | |
| Type of light so | urce: | | | | | |
| Lighting technology used: | | LED | Non-directional or directional: | NDLS | | |
| Light source cap-type | | LED | | | | |
| (or other electric interface) | | | | | | |
| Mains or non-mains: | | NMLS | Connected light source (CLS): | Yes | | |
| Colour-tuneable light source: | | Yes | Envelope: | - | | |
| High luminance light source: | | No | | | | |
| Anti-glare shield: | | No | Dimmable: | Yes | | |
| | | Product para | | T | | |
| Parameter | | Value | Parameter | Value | | |
| _ | | General product | <u>-</u> | | | |
| Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer | | 2 | Energy efficiency class | G | | |
| Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | | 100 in Wide cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000 | | |
| On-mode power (P _{on}), expressed in W | | 2,0 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 | | |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | 0,00 | Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set | 80 | | |
| Outer dimen- | Height | 150 | Spectral power dis- | See image | | |
| sions without separate con- trol gear, light- ing control | Width Depth | 100 | tribution in the range 250 nm to 800 nm, at full-load | in last page | | |

| parts and non- lighting con- trol parts, if any (millime- tre) | | | | | | |
|--|------|------------------------------|-------|--|--|--|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - | | | |
| | | Chromaticity coordi- | 0,441 | | | |
| | | nates (x and y) | 0,415 | | | |
| Parameters for LED and OLED light sources: | | | | | | |
| R9 colour rendering index value | 0 | Survival factor | 0,90 | | | |
| the lumen maintenance factor | 0,96 | | | | | |

(a)'-': not applicable; (b)'-': not applicable;

